



Trailer ID	AU35-B/S-13.7-HD-3WT-FKH3/KT-LPV-RT
Trailer Model	AU35 Heavy Duty Drop Deck "B" Semi-Trailer Road Train
Dimensions	<p>Trailer Length: 13,730mm Top Deck Height: 1,575mm Drop Deck Height: 1,065mm Trailer Width: 2,500mm King Pin Location: 1,430mm Coupler Height: 1,270mm Suspension Location: 9400mm</p>
Chassis	<p>KHITCH 50mm bolt-on kingpin with 10mm skid plate Flush coaming rail FUWA A400 Series 2 speed landing legs with rocker feet 3 Way Twist Locks: 1 x 20', 2 x 20' and 1 x 40' Flush coaming with tie rails & gate pockets on each side Front and rear coamings with tie rails & pockets for load racks Front & rear connection plates w/PBR air couplings Top Deck 3mm steel chequer plate forklift rated floor with access steps Bottom Deck 5mm steel chequer plate forklift rated floor with access steps Rear bumper with load rack and rope rail Rear bumper bar colour: Traffic Red (RAL3020) fitted with dock rubber Front & rear coamings and bumper bar colour: Traffic Red (RAL3020) Provision for road train with air & electrical to rear Twelve (12) recessed chain tie down points – Claw feet- 6 of each on both sides</p>
Accessories	<p>Grey colour swing type dual spare tyre carrier Eleven (11) load binder ratchet winches (3 recessed at front and 7 on sliding track – 11mt straps) with (3) loose hand ratchets to be used for front/rear and side of trailer. Two (2) off raiser blocks inside toolbox Conspicuity plates and long vehicle and road train signage on rear Six (6) off CIMC Ferry Lashing in Grey colour gate carrier with two (2) gate load binders One (1) low profile steel toolbox 1200 x 450 x 450 w/Stainless steel 'T' handles Twelve (12) CIMC lightweight steel gates w/3 spades front sides 1500mm & rear sides 2000mm Two (2) off lightweight load racks (Front 1500mm & Rear 2000mm)</p>
Axles & Suspension	<p>K-Hitch 127mm drum brake round axles with parallel bearings K-Hitch tri-axle underslung air bag suspension KT Series Auto Slack Adjusters fitted Hubodometer fitted on centre axle roadside</p>
Brakes	WABCO Load Proportioned (LSV) system to ADR 38/04
Wheels & Tyres	<p>Twelve (12) off 275/70R22.5 Tyres Twelve (12) off 10 Stud 285 PCD Steel rims Angle type bolt on mudguard with anti-spray CIMC rubber mudflaps</p>
Electrical System	<p>LED Multi-volt lighting to ADR 13 7-pin standard and heavy duty socket at front and rear Philips heavy-duty wiring loom with weatherproof connectors rated for road train application</p>
Paint	<p>Chassis, twist lock beams and bumper bar finished in 2K-PU Stock Colours: Monza Red (RAL3002) or Sapphire Blue (RAL5003)</p>
Tare Weight	Approx. 9,520kg based on standard specification