



Trailer ID	AU70-B/S-10.4-FKH3/KT-LPV-RT
Trailer Model	GTE 10.4m (34') Steel Grain Tipper (Chassis Tipper)
Dimensions	Trailer Dimension: 10,772mm (34') L x 2,500mm (W) x 3,700mm (H) Capacity: 48 m3 King Pin Location: 1,150mm Coupler Height: 1,290mm Suspension Location: 7,550mm Road Train Tow Coupling Height: 850mm
Chassis	JOST 50mm bolt-on kingpin with 10mm skid plate JOST A400 Series 2 speed landing legs with rocker feet 1' hydraulic hose fitted to front with coupling Road train towing cross member fitted with air/electric to rear (Provision)
Body	Side: 3mm mild steel body, 1925mm (6") height Front & Floor: 3mm mild steel floor Tailgate: Two way tailgate with aluminum grain door Manual PVC roll over grain tarp fitted to your colour Ladders fitted in front and rear Boom and shovel rack fitted in the front panel HYVA 50 tonne hoist, internal mount
Axles & Suspension	K-Hitch 127mm drum brake round axles with parallel bearings K-Hitch tri-axle underslung air bag suspension KT Series Auto Slack Adjusters fitted Hubodometer fitted on centre axle roadside
Brakes	WABCO Load Proportioned (LSV) system to ADR 38/04 Dump valve – Front connection plate w/PBR air couplings
Wheels & Tyres	Twelve (12) off 11R22.5 Tyres Twelve (12) off 10 Stud 285 PCD Steel rims Heavy duty rubber mud guard fitted over tri-axle group
Electrical System	LED Multi-volt lighting to ADR 13 7-pin socket at front Philips heavy-duty wiring loom with weatherproof connectors and conduit
Paint	Chassis, twist lock beams and bumper bar finished in 2K-PU Monza Red (RAL 3002) Body finished in 2K-PU White (RAL9003)
Tare Weight	Approx. 7,600kg based on standard specification