



Trailer ID	AU70-B/S-24GP-FKH3/KT-LPV-RT
Trailer Model	GTE 24m3 General Purpose Tipper
Dimensions	<p>Trailer Dimension: 9,000mm (L) x 2,500mm (W) x 3,200m (H)</p> <p>Capacity: 24 m3</p> <p>King Pin Location: 1,010mm</p> <p>Coupler Height: 1,270mm</p> <p>Suspension Location: 5,700mm</p> <p>Road Train Tow Coupling Height: 850mm</p>
Chassis	<p>JOST 50mm bolt-on kingpin with 10mm skid plate</p> <p>JOST A400 Series 2 speed landing legs with rocker feet</p> <p>Road train towing cross member fitted with air/electric to rear (Provision)</p> <p>1' hydraulic hose fitted to front with coupling</p>
Body	<p>3mm BHN450 high tensile steel side wall</p> <p>4mm BHN450 high tensile steel front & floor</p> <p>3mm BHN450 high tensile steel one way tailgate</p> <p>End to End remote control tarp system fitted</p> <p>Ladders fitted in front</p> <p>Boom and shovel rack fitted in the front panel</p> <p>HYVA 50 tonne hoist</p>
Axles & Suspension	<p>K-Hitch 127mm drum brake round axles with parallel bearings</p> <p>K-Hitch tri-axle overslung air bag suspension KT Series</p> <p>Auto Slack Adjusters fitted</p> <p>Hubodometer fitted on centre axle roadside</p>
Brakes	<p>WABCO Load Proportioned (LSV) system to ADR 38/04</p> <p>Dump valve – Front connection plate w/PBR air couplings</p>
Wheels & Tyres	<p>Twelve (12) off 11R22.5 Tyres</p> <p>Twelve (12) off 10 Stud 285 PCD Steel rims</p> <p>Plastic mud guard fitted over tri-axle group, Color: Black</p>
Electrical System	<p>LED Multi-volt lighting to ADR 13</p> <p>7-pin socket at front</p> <p>Philips heavy-duty wiring loom with weatherproof connectors and conduit</p>
Paint	<p>Chassis, twist lock beams and bumper bar finished in 2K-PU Monza Red (RAL 3002)</p> <p>Body finished in 2K-PU White (RAL9003)</p>
Tare Weight	Approx. 6,180kg based on standard specification