


CIMC Vehicle Australia Pty Ltd

ABN 53 124 976 156

Toll free 1300 20 2462

Driving New Value – Moving the World



Trailer ID AU10-B/S-HC-3WT-FKH3/KT-SLP-LPV-RT

Trailer Model 40' Standard 3 Way Skeletal "B" Trailer

Dimensions Trailer Length: 12,135mm

Twist Lock Height: 1,405mm Trailer Width: 2,440mm King Pin Location: 1,100mm Coupler Height: 1,270mm Suspension Location: 8,600mm

Chassis KHITCH 50mm bolt-on kingpin with 8mm skid plate

JOST A400 Series 2 speed landing legs with rocker feet

Side Loader Pads & side intrusion cables fitted 3 Way Twist Locks: 1 x 20', 2 x 20' and 1 x 40'

Rear bumper bar incorporated on rear twist lock beam with recessed lights

Solid dock rubbers fitted

Provision for Road Train, air & electrical to rear (RingFeder not fitted)
Two pieces hinged long vehicle & road train signage on rear infill panels

Conspicuity plates at rear

Axles & Suspension K-Hitch 127mm drum brake round axles with parallel bearings

K-Hitch tri-axle underslung air bag suspension KT Series

Auto Slack Adjusters fitted

Hubodometer fitted on centre axle roadside

Brakes WABCO Load Proportioned (LSV) system to ADR 38/04

Dump valve - Front connection plate w/PBR air couplings

Wheels & Tyres Twelve (12) off 11R22.5 Tyres

Twelve (12) off 10 Stud 285 PCD Steel rims

Plastic radius guards with anti-spray CIMC rubber mudflaps

Electrical System LED Multi-volt lighting to ADR 13

7-pin socket at front

Philips heavy-duty wiring loom with weatherproof connectors and conduit

Paint Chassis, twist lock beams and bumper bar finished in 2K-PU

Stock Colours Monza Red (RAL3002) or Sapphire Blue (RAL5003)

Tare Weight Approx. 5,540kg based on standard specification