



Trailer ID	AU30-B/S-13.7-3WT-FKH3/KT-LPV-RT
Trailer Model	AU30 Flat Deck "B" Semi-Trailer Road Train
Dimensions	Trailer Length: 13,730mm Deck Height: 1,527mm Trailer Width: 2,500mm King Pin Location: 1,430mm Coupler Height: 1,270mm Suspension Location: 9400mm
Chassis	JOST 50mm bolt-on kingpin with 8mm skid plate JOST A400 Series 2 speed landing legs with rocker feet 3 Way Twist Locks: 1 x 20', 2 x 20' and 1 x 40' 24mm raised pressed coaming with tie rails & gate pockets on each side Front and rear coamings with tie rails & pockets for load racks Front & rear connection plates w/PBR air couplings 3mm steel chequer plate forklift rated floor with access steps Rear bumper bar incorporated on rear twist lock beam with recessed lights Rear bumper bar colour: Monza Red (RAL3002) fitted with dock rubber Front & rear coamings and bumper bar colour: Monza Red (RAL3002) Provision for road train with air & electrical to rear (RingFeder not fitted)
Accessories	Galvanized dual spare tyre carrier Eleven (11) off load binder ratchet winches (3 recessed at front and 8 on sliding track – 9mt straps) Eight (8) off raiser blocks inside toolbox Conspicuity plates and long vehicle signage on rear Six (6) off CIMC lifting points in chassis colour Galvanised gate carrier with two (2) gate load binders One (1) Jumbo steel toolbox 1200 x 700 x 450 w/Stainless steel 'T' handles Twelve (12) off 1500mm CIMC lightweight steel gates w/3 spades Two (2) off 1500mm lightweight load racks (Front & Rear)
Axles & Suspension	K-Hitch 127mm drum brake round axles with parallel bearings K-Hitch tri-axle overslung air bag suspension KT Series Auto Slack Adjusters fitted Hubodometer fitted on centre axle roadside
Brakes	WABCO Load Proportioned (LSV) system to ADR 38/04
Wheels & Tyres	Twelve (12) off 11R22.5 Tyres Twelve (12) off 10 Stud 285 PCD Steel rims Angle type bolt on mudguard with anti-spray CIMC rubber mudflaps
Electrical System	LED Multi-volt lighting to ADR 13 7-pin standard socket at front and rear Philips heavy-duty wiring loom with weatherproof connectors and conduit rated for road train application
Paint	Chassis colour in Traffic Red (RAL3020) – KTL Painting
Tare Weight	Approx. 7,920kg based on standard specification