



Trailer ID	AU10-ULP-48'C-EBA-3WT-FKH3/KT-LPV
Trailer Model	45' Ultra Low Profile Skeletal Trailer with Extendable Bumper
Dimensions	<p>Trailer Length: 13,716mm (45') or 14,630mm (48')</p> <p>Twist Lock Height: 1,100mm</p> <ul style="list-style-type: none"> At 1220mm coupler height with 11R22.5 tyres, carry up to 9'10" container At 1025mm coupler height with 255/70R22.5 tyres, carry up to 10'6" container <p>Trailer Width: 2,440mm</p> <p>King Pin Location: 1,100mm</p> <p>Coupler Height: 1,025mm</p> <p>Suspension Location: 9,500mm</p>
Chassis	<p>700Mpa high tensile steel chassis with 75mm deep front twist lock beam</p> <p>JOST 50mm bolt-on kingpin with 8mm skid plate</p> <p>JOST A400 Series 2 speed landing legs with rocker feet</p> <p>Side intrusion cables fitted</p> <p>3 Way Twist Locks: 1 x 20', 2 x 20', 1 x 40', 1 x 45', 1 x 48'</p> <p>Rear bumper bar incorporated on rear twist lock beam with recessed lights</p> <p>Air Operated extendible bumper bar with solid dock rubbers</p>
Axles & Suspension	<p>K-Hitch 127mm drum brake round axles with parallel bearings</p> <p>K-Hitch tri-axle underslung air bag suspension KT Series</p> <p>Auto Slack Adjusters fitted</p> <p>Hubodometer fitted on centre axle roadside</p>
Brakes	<p>WABCO Load Proportioned (LSV) system to ADR 38/04</p> <p>Raise and Lower Valve fitted</p>
Wheels & Tyres	<p>Twelve (12) off 11R22.5 Tyres</p> <p>Twelve (12) off 10 Stud 285 PCD Steel rims</p> <p>Plastic radius guards with anti-spray CIMC rubber mudflaps</p>
Electrical System	<p>LED Multi-volt lighting to ADR 13</p> <p>7-pin socket at front</p> <p>Philips heavy-duty wiring loom with weatherproof connectors and conduit</p>
Paint	<p>Chassis, twist lock beams and bumper bar finished in 2K-PU</p> <p>Stock Colours: Monza Red (RAL3002) or Sapphire Blue (RAL5003)</p>
Tare Weight	Approx. 5,740kg based on standard specification